

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

**P.O. BOX 147,
MAIDSTONE, ME14 2LA.**

**TEL:01622 832777
FAX:01622 832507**

sales@airclean.co.uk www.airclean.co.uk

Grease Filters (Standard Mesh Type)

Applications

Grease filters are generally installed in canopies above ranges of cooking equipment, to eliminate or greatly reduce the problem of cooking oil etc., being drawn into and settling in the extract ductwork.

This significantly reduces the frequency of expensive duct cleaning, and offers some protection against grease-fire hazards.

AIRCLEAN now have many thousands of these filters operating satisfactorily in leading restaurants, hotel kitchens and ships galleys.

Construction

The filtration media is crimped galvanised knitted wire mesh, which is enclosed in either an aluminium or galvanised channel frame. Galvanised retaining meshes are fitted to both faces, and corner gussets provide rigidity.

Handles are normally desirable on grease filters for ease of removal and cleaning, but these are optional.

All stainless filters, or galvanised media with stainless frames, are also available.



Technical

Filter classification :

Typically G2 to EN779

Recommended face velocity :

3.0 m/s (600 ft/min)

Resistance to Airflow

m/s fpm	Face Velocity							
	1.5 300		2.0 400		2.5 500		3.0 600	
Pressure Drop	Pa	"wg	Pa	"wg	Pa	"wg	Pa	"wg
1" Panel	8	0.03	12	0.05	18	0.07	25	0.10
2" Panel	12	0.05	18	0.07	25	0.10	33	0.13

The company reserves the right to change specifications without notice. E&OE

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

Capacity Chart

Data based on Face Velocity of 2.5 m/s (500 fpm)

SIZE	SIZE	Flow Rate
OT Inches	Actual mm	m ³ /s
10 x 10	242 x 242	0.15
12 x 12	289 x 289	0.21
15 x 15	369 x 369	0.34
16 x 16	394 x 394	0.39
18 x 9	445 x 216	0.24
18 x 18	445 x 445	0.50
20 x 10	495 x 242	0.30
20 x 16	495 x 394	0.49
20 x 20	495 x 495	0.62
25 x 16	620 x 394	0.62
25 x 20	620 x 495	0.77
24 x 24	594 x 594	0.91

Actual Face Size = Nominal Size less 12mm (0.5")
Actual thickness = Nominal thickness less 3mm (0.125")

Cleaning

It is important that grease filters are cleaned regularly (according to use). This can be carried out by steam cleaning, washing in an automatic dishwasher, or by immersion in a solution specially designed for this purpose.

AIRCLEAN have cleaning crystals and a range of tanks available which are described, in leaflet AC3/8.



The company reserves the right to change specifications without notice. E&OE

Code AC3/1b Ref 01/11