

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

Activated Carbon Filters - Use and Selection

Carbon panels are normally supplied and fitted with an aluminium frame and can be made to any reasonable size to match existing panels of all makes. The depth of panel is restricted by our own imposed limits of not less than 10mm and not greater than 60mm Actual depth. Capacities shown for Panels & 'Discarb' units are based on a dwell time of 0.1 seconds, which is the normally accepted minimum for most applications.



Air Flow = Width x Length x Depth/Dwell Time
or Air Flow = Width x Length x Face Velocity

As a guide,

Nominal thickness	Actual thickness	Pressure drop	Face velocity m/s
25mm	22mm	45 Pa	0.22 (43fpm)
22mm	19mm	40 Pa	0.19(37fpm)

For 'heavier' odours i.e. Indian cooking odours, a contact time of 0.3 seconds is recommended, which will effectively reduce the Face Velocity and rating to one third..

Where hot air is being filtered (e.g. extract from cooker hoods) the carbon cells should be positioned as far from the heat source as possible.

Air stream temperatures must be maintained below 40Deg C. and humidity levels below 80% RH. If temperatures or humidity in excess of either of these figure are anticipated, the airstream must be treated to ensure compliance. Additional fresh air, and or cooling may be considered as suitable measures.

Pre-filters should be fitted in the ventilation system to protect the carbon filters in all installations from particulate contamination. We do not consider a glass panel to be suitable and recommend a filter having a minimum grade of F5 to EN779.

Some cooking operations give off large amounts of smoke, which is extremely detrimental if allowed to reach the carbon filters(smoke is a particulate).

In most cases this can be overcome by the use of a good quality pre-filter. e.g. an F8 Grade Bag Filter or better, depending upon circumstances. In some instances a HEPA Filter grade H14 is necessary.

'Discarb' Cells can be 'tailor-made' to any reasonable size to fit ducting, air-handling units etc.

Activated carbons are graded as follows :

Grade 20 Activity Carbons are rated 30% on their ability to 'adsorb' carbon tetrachloride (CTC) in testing; and have a typical surface area per weight of between 700-800 m²/g by the BET N2 method (the area being a measure of the area of the walls of the cavern like structure of the activated carbon): Bulk density is between 0.55 - 0.59 g/cc

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

Grade 50 Activity Carbons are rated 55% on their ability to 'adsorb' carbon tetrachloride (CTC) in testing; have a typical surface area per weight of between 1100-1200 m²/g by the BET N2 method (the area being a measure of the area of the walls of the cavern like structure of the activated carbon): Bulk density is between 0.49 - 0.53 g/cc

Guide to the Gaseous Adsorption Level for Grade 50 Activity Carbon

A = 20 - 50% adsorption
B = 10 - 20%

C = 1 - 10%
D = under 1%

	Chemical	Index	Common Source of Chemical
1	ACETAHALDEHYDE	C	REAGENT
2	ACETIC ACID	A	REAGENT, SOUR VINEGAR
3	ACETIC ANHYDRIDE ACID	A	
4	ACETONE	B	SOLVENT
5	ACETYLENE	D	WELDING AND CUTTING
6	ACROLEIN	B	
7	ACRYLALDEHYDE	B	AEROLEIN, BURNING FATS
8	ACRYLIC ACID	A	
9	ADHESIVES	A	
10	AMINES	C	
11	AMMONIA	D	
12	AMYL ACETATE	A	LACQUER SOLVENT
13	AMYL ALCOHOL	A	FUSEL OIL
14	AMYL ETHER	A	
15	ANILINE	A	
16	ANIMAL ODOURS	A	
17	BENZALDEHYDE	A	
18	BENZENE	A	BENZOL, PAINT SOLVENT & REMOVER
19	BROMINE	A	
20	BUTADIENE	C	
21	BUTANE	C	HEATING GAS
22	BUTYL ACETATE	A	LACQUER SOLVENT
23	BUTYL ALCOHOL	A	SOLVENT
24	BUTYL CHLORIDE	A	SOLVENT
25	BUTYL ETHER	A	SOLVENT
26	BUTYLENE	B	
27	BUTYRALDEHYDE	B	PRESENT IN INTERNAL COMBUSTION EXHAUST - DIESEL
28	BUTYRIC ACID	A	
29	BUTYRIC ACID	A	SWEAT, BODY ODOUR
30	CAMPHOR	A	
31	CAPROALDEHYDE	A	
32	CAPRYLIC ACID	A	ANIMAL ODOUR

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

33	CARBOLIC ACID	A	
34	CARBON DIOXIDE	A	
35	CARBON DISULPHIDE	B	
36	CARBON MONOXIDE	D	
37	CARBON TETRACHLORIDE	A	SOLVENT,CLEANING FLUID,FIRE EXTINGUISHER
38	CELLOSOLVE ACETATE	A	
39	CELLOSOLVE ETHER	A	
40	CHLORINE	B	
41	CHLORO PICRIN	A	
42	CHLOROBENZINE	A	
43	CHLOROBUTADEINE	A	
44	CHLOROFORM	A	
45	CHLORONITROPROPANE	A	
46	CITRUS FRUITS	A	
47	COOKING ODOURS	A	
48	CRESOL	A	WOOD PRESERVATIVE
49	CRONTONALDEHYDE	A	SOLVENT,TEAR GAS
50	CYCLOHEXANE	A	
51	CYCLOHEXANOL	A	
52	DECANE	A	INGREDIENT OF KEROSENE
53	DEGREASING SOLVENTS	A	
54	DEODERISERS	B	
55	DETERGENTS	A	
56	DIBROMOETHANE	A	
57	DICHLOROBENZINE	A	
58	DICHLORODIFLUORO ETHANE	A	
59	DICHLORODIFLUORO METHANE	B	
60	DICHLOROETHANE	A	
61	DICHLOROETHYL ETHER	A	
62	DICHLOROETHYLENE	A	
63	DICHLOROMETHANE	A	
64	DICHLOROMONOFUORO METHANE	B	
65	DICHLOROPROPANE	A	
66	DICHLOROTETRAFLUORO ETHANE	B	
67	DIETHYL AMINE	B	
68	DIETHYL ANILINE	A	
69	DIETHYL KETONE	A	SOLVENT
70	DIMETHYL AMINE	B	
71	DIMETHYL SULPHATE	A	
72	DIOXAN ETHER	A	
73	DIPROPYL KETONE	A	
74	ETHANE	D	
75	ETHYL ACETATE	A	LACQUER SOLVENT
76	ETHYL ACRYLATE	A	
77	ETHYL ALCOHOL	A	GRAIN ALCOHOL Code AC6/1c Ref 05/06

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

78	ETHYL AMINE	B	
79	ETHYL BROMIDE	B	
80	ETHYL CHLORIDE	B	REFRIGERANT, ANESTHETIC
81	ETHYL ETHER	B	MEDICAL ETHER, REAGENT
82	ETHYL FORMATE	B	
83	ETHYL MERCAPTAN	A	GARLIC, ONION, SEWER
84	ETHYLENE	D	MORE RETENTIVITY BY REACTION,
85	ETHYLENE CHLOROHYDRIN	A	
86	ETHYLENE DICHLORIDE	A	
87	ETHYLENE OXIDE	B	
88	EXYLENE	A	
89	FLUOROTRICHLOROMETHANE	B	
90	FORMALDEHYDE	C	DISINFECTANT, PLASTIC INGREDIENT
91	FORMIC ACID	B	REAGENT
92	FREON	C	
93	GARLIC	A	
94	HEPTANE	A	INGREDIENT OF GASOLINE
95	HEPTYLENE	C	
96	HEXANE	B	INGREDIENT OF GASOLINE
97	HOSPITAL ODOURS	A	
98	HUMAN ODOURS	A	
99	HYDROGEN BROMIDE	C	
100	HYDROGEN CHLORIDE	C	
101	HYDROGEN CYANIDE	B	
102	HYDROGEN FLUORIDE	C	
103	HYDROGEN IODIDE	B	
104	HYDROGEN SULPHIDE	C	OXIDIZES TO INCREASE RETENTIVITY CONSIDERABLY
105	INDOLE	A	IN EXCRETIA
106	IODINE	A	
107	IODOFORM	A	ANTISEPTIC
108	ISO BUTANE	B	
109	ISOPROPYL ACETATE	A	LACQUER SOLVENT
110	ISOPROPYL ALCOHOL	A	SOLVENT
111	ISOPROPYL ETHER	A	SOLVENT
112	LACTIC ACID	A	
113	LEATHER	A	
114	MERCAPTANS	A	
115	MESITYL OXIDE	A	
116	METHANE	D	
117	METHANOL (METHYL)	B	

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

118	METHYL ACETATE	B	SOLVENT
119	METHYL ACRYLATE	A	
120	METHYL ALCOHOL	B	WOOD ALCOHOL
121	METHYL BROMIDE	B	
122	METHYL BUTYLKETONE	A	
123	METHYL CELLOSOLVE	Q	
124	METHYL CHLORIDE	B	REFRIGERANT
125	METHYL ETHER	A	
126	METHYL FORMATE	B	
127	METHYL ETHYLKETONE	A	SOLVENT
128	METHYL FORMATE	B	
129	METHYL ISOBUTYLKETONE	A	SOLVENT
130	METHYL MERCAPTAN	A	
131	METHYLENE CHLORIDE	A	
132	MONOCHLOROBENZINE	A	
133	MONOFLUOROTRICHORO METHANE	B	
134	n-DECANE	D	
135	n-HEPTANE	D	
136	n-NONANE	D	
137	n-OCTANE	D	
138	n-OCTYLENE	D	
139	NAPHTHALENE	A	REAGENT, MOTH BALLS
140	NICOTINE	A	TOBACCO
141	NITRIC ACID FUMES	B	
142	NITROBENZENE	A	OIL OF BITTER ALMONDS, OIL OF MIRBANE
143	NITROETHANE	A	
144	NITROGEN DIOXIDE	C	HYDROLYZES TO INCREASE RETENTIVITY
145	NITROGLYCERENE	A	
146	NITROMETHANE	A	
147	NITROPROPANE	A	
148	NITROTOLUENE	A	
149	NONANE	A	INGREDIENT OF KEROSENE
150	OCTANE	A	INGREDIENT OF GASOLENE
151	OZONE	A	GENERATED BY ELECTRICAL DISCHARGE
152	PALMITIC ACID	A	PALM OIL
153	PARADICHLOROBENZENE	A	
154	PENTANE	B	LIGHT NAPHTHA

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

155	PERCHLOROETHYLENE	A	
156	PERFUMES	A	
157	PETROL	A	
158	PHENOL ACID	A	CARBOLIC ACID, PLASTIC INGREDIENT
159	PHOSGENE	B	
160	PLASTIC	A	
161	POULTRY ODOURS	A	
168	PROPYL CHLORIDE	A	
169	PROPYL ETHER	A	
170	PROPYL MERCAPTAN	A	
171	PROPYLENE	B	COAL GAS
172	PURIFYING ODOURS	B	
173	PUTRESCINE	A	DECAYING FLESH
174	PYRIDINE	A	BURNING TOBACCO
175	RANCID OILS & FATS	A	
176	RESINS	A	
177	RUBBER	A	
178	SKATOLE	A	IN EXCRETA
179	STABLE ODOURS	A	
180	STALE ODOURS	A	
181	STYRENE MONOMER	A	
182	SULPHUR TRIOXIDE	B	HYDROLYZES TO SULPHURIC ACID
183	SULPHUR DIOXIDE	C	OXIDIZES TO SULPHUR TRIOXIDE, COMMON IN CITY ATMOSPHERES
184	SULPHURIC ACID	A	
185	TAR ODOURS	A	
186	TETRACHLORO ETHANE	A	
187	TETRACHLORO ETHYLENE	A	
188	TETRAHYDROTHIOPHENE	A	
189	TOBACCO SMOKE	C	
190	TOILET ODOURS	A	
191	TOLUENE	A	MANUFACTURE OF TNT
192	TOLUIDINE	A	

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

193	TRICHLORO ETHYLENE	A	
194	TURPENTINE	A	SOLVENT
195	UREA	A	
196	URIC ACID	A	
197	VALERALDEHYDE	A	
198	VALERIC ACID	A	SWEAT, BODY ODOUR, CHEESE
199	VALERIC ALDEHYDE	A	
200	VARNISH	A	
201	VENTILATION SYSTEMS	A	
202	VINEGAR	A	
203	VINYL CHLORIDE	B	
204	WOOD ALCOHOL	B	
205	XYLENE	A	SOLVENT

Free Carbon Testing Service

It is extremely difficult to calculate in advance the life expectancy of an activated carbon filter.

Generally speaking, accurate information regarding concentration and details of all contaminants in the airstream are not available and in any case these are often constantly changing.

However, reasonably accurate life expectancy levels can be obtained by a method known as CTC testing.

Either a small sample of carbon from one of the cells, or a complete panel, should be returned to us together with the date of installation. From this information the contamination level will be assessed in the laboratory, which will indicate the likely remaining useful life of the carbon.

This testing service is totally free of charge to our customers.

The company reserves the right to change specifications without notice. E&OE