

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

Activated Carbon Unit

Applications

- Odour Control
- Residual ozone collection
- Combined fan / filter unit for extract systems

Construction

Manufactured from anodised aluminium framework with 25mm thick double skinned panels filled with 60kg/m³ mineral wool insulation. The air stream enters at the top of the unit passing vertically down through the Grade F5 Bag Filters into the Activated Carbon Cell yielding a 0.1 second contact time, then into the fan. The air is then discharged from the fan into the noise attenuator duct travelling vertically up to the spigotted discharge connection. The fan speed is controlled by an electrical inverter to provide the required airflow through the units.

Technical

Airflow: 1m³/s

External Resistance Available: 200Pa

Contact Time at Rated Airflow: 0.1 seconds



Manufacture and Cleaning

The unit is installed with an activated carbon test cell, which when returned along with the number of hours it has been run for, can be analysed in our test facility to provide an estimate as to the remaining life of the carbon filter.

The Pre Filter should be changed when the pressure drop across the filter measured by the magnehelic pressure gauge reads twice the "as installed" pressure for the filter.

For further technical details on this product please contact Airclean.

AIRCLEAN

YOUR AIR FILTER MANUFACTURER

P.O. BOX 147,
MAIDSTONE, ME14 2LA.

TEL:01622 832777
FAX:01622 832507

sales@airclean.co.uk www.airclean.co.uk

Schematics

